

1	RESPONSIBLE ORGANIZATION						6	SPECIFICATION IDENTIFICATIONS			
2	LINEAR MOTION TYPE MOTOR OPERATED VALVE ASSEMBLY Device Specification						7	Document no			
3							8	Latest revision	Date		
4							9	Issue status			
5							10				
11	VALVE BODY AND BONNET						75	ACTUATOR Continuation			
12	Body type						76	Motor contactor type			
13	Bonnet style						77	Motor thermal protection			
14	Inlet conn nominal size				Rating		78	Motor phase protection			
15	Outlet conn nominal size				Rating		79				
16	End conn termn type				Style		80	CONTROL MODULE			
17	Flange facing finish						81	Enclosure type			
18	Stem seal type						82	Operation style			
19	Face-to-face standard						83	Input signal type			
20	Yoke boss diameter						84	Enclosure type nsl/class			
21	Body and bonnet material						85	Control mode			
22	Lining material						86	Digital communication std			
23	Body/Bonnet bolting matl						87	Internal power supply			
24	Packing flg bolting matl						88	Space heater type			
25	Gasket material						89	Output speed control			
26	Packing material						90	Auxiliary control power			
27	Bellows seal material						91	Open/Close control			
28							92	Local/Stop/Remote cont			
29	VALVE TRIM						93	Local operator interface			
30	Closure member type						94	Signal termination type			
31	Trim style						95	Cert/Approval type			
32	Inherent characteristic						96	ESD control mode			
33	Seat ring type						97	Failure/Diagnostic action			
34	Flow direction force						98	Interlock/Inhibit mode			
35	Port/Orifice diameter						99	Diagnostics capabilities			
36	Stem diameter				Travel		100	Motor reversal protection			
37	Closure member material						101	Enclosure material			
38	Seat ring material						102	Hardware material			
39	Stem material						103				
40	Cage material						104				
41	Guide/Retainer material						105	POSITION SWITCH OR TRANSMITTER			
42	Guide bushing material						106	Output signal type			
43	Hard facing/coating						107	Sensor style			
44							108	Contacts ac rating			
45	GEAR REDUCER						109	Contacts dc rating			
46	Gear reducer type						110	Signal power source			
47	Position tolerance						111	Contacts arrangement			
48	Nominal size						112	Integral indicator style			
49	Mounting base nom size				Standard		113	Position light colors			
50	Output nominal speed						114				
51	Handwheel gear ratio						115	TORQUE SWITCH OR TRANSMITTER			
52	Gearbox ratio						116	Output signal type			
53	Rated output torque				Thrust		117	Sensor style			
54	Linear speed						118	Contacts ac rating			
55	Manual operator type						119	Contacts dc rating			
56	Stem coupling style						120	Signal power source			
57	Stem nominal diameter				Lead of screw		121	Contacts arrangement			
58	Handwheel diameter						122	Integral indicator style			
59	Handwheel orientation						123	Protection feature			
60	Travel stops						124				
61	Bevel pinion material						125	AUXILIARY INPUTS AND OUTPUTS			
62	Bevel gear matl						126	Configuration type			
63	Housing material						127	Aux signal type			
64	Bushing/Coupling/Nut matl						128	Output signal type			
65	Lubricant material						129	Status contacts ac rating			
66							130	Status contacts dc rating			
67							131	Alarm contacts ac rating			
68	ACTUATOR						132	Alarm contacts dc rating			
69	Actuator type						133	Input signal power source			
70	Motor style						134	Output signal pwr source			
71	Motor nominal speed				number of poles		135	Status contacts arr			
72	Power supply						136	Alarm contacts arr			
73	Insulation class rating						137				
74	Motor phase style						138				
Rev	Date	Revision Description				By	Appv1	Appv2	Appv3	REMARKS	

1	RESPONSIBLE ORGANIZATION			LINEAR MOTION TYPE MOTOR OPERATED VALVE ASSEMBLY Device Specification			6	SPECIFICATION IDENTIFICATIONS			
2							7	Document no			
3							8	Latest revision	Date		
4							9	Issue status			
5							10				
211	PERFORMANCE CHARACTERISTICS						246	PHYSICAL DATA			
212	Max press at design temp			At			247	Estimated weight			
213	Min working temperature			Max			248	Face-to-face dimension			
214	Max pressure drop						249	Overall height			
215	Maximum starts per hour						250	Removal clearance			
216	Positioning accuracy			Ref			251	Signal conn nominal size	Style		
217	Position accuracy rating			Ref			252	Mfr reference dwg			
218	Torque accuracy rating			Ref			253				
219	Torque adjustment LRL			URL			254				
220	Max starting current						255				
221	Rated flow coef type		Coef		Xt		256				
222	Rated factor FI			Sigma mr			257				
223	Rated seat leakage class						258				
224	Max valve reqd torque			Thrust			259				
225	Design life cycles						260				
226	Min ambient working temp			Max			261				
227							262				
228							263				
229	ACCESSORIES						264				
230	Isolation switch						265				
231	Local control station						266				
232	Auxiliary power device						267				
233							268				
234							269				
235	SPECIAL REQUIREMENTS						270				
236	Custom tag						271				
237	Reference specification						272				
238	Special preparation						273				
239	Compliance standard						274				
240	Construction code						275				
241	Calculation report						276				
242	Software program						277				
243	Service design						278				
244							279				
245							280				
310	CALIBRATIONS AND TEST						INPUT OR TEST		OUTPUT OR SCALE		
311	TAG NO/FUNCTIONAL IDENT	MEAS/SIGNAL/SCALE				LRV	URV	ACTION	LRV	URV	
312		Position input-Travel									
313		Close sw energized-Travel									
314		Open sw energized-Travel									
315		Position-Output									
316		Torque-Output									
317		Position-Scale									
318		Aux input 1-Output									
319		Aux input 2-Output									
320		Aux input 3-Output									
321		Aux input 4-Output									
322		Position close sw-Output									
323		Position open sw-Output									
324		Torque close sw-Output									
325		Torque open sw-Output									
326		Aux output 1-Output									
327		Aux output 2-Output									
328		Aux output 3-Output									
329		Aux output 4-Output									
330		Failure signal-Output									
331											
332	COMPONENT IDENTIFICATIONS										
333	COMPONENT TYPE		MANUFACTURER			MODEL NUMBER					
334											
335											
336											
337											
338											
Rev	Date	Revision Description			By	Appv1	Appv2	Appv3	REMARKS		